






Наименование, артикул, эскиз						Цвет профиля	Код по каталогу	Масса, кг/м.п.	Длина хлыста, м.п.	Внешний периметр, мм	Момент инерции, см ⁴		Момент сопротивления, см ³		Количество в упаковке		Масса в упаковке брутто, кг
											Jx	Jy	Wx	Wy	шт.	м.п.	
Профиль штапика АУРС С48.0608А 						A00-D6	104098808	0.346	6.5	189.1	-	-	-	-	12	78	27.8
W	HS	VS	TD	PVC	OUT												
●			●	●	●												
АУРС С48.0611 Профиль отлива 						00 RAL9016 RAL9006 A00-D6	10402400 10402421 10402431 104024808	0.186	6.5	88.3	-	-	-	-	12	78	15 15.8 15.8 15
W	HS	VS	TD	PVC	OUT												
●			●	●	●												
Профиль тяги АУРС С48.0612 						A00-E6 A05-E6	104025806 104025856	0.133	6.5	49.3	-	-	-	-	24	156	212 212
W	HS	VS	TD	PVC	OUT												
●	●	●	●		●												
АУРС С48.0614 Профиль выравнивающий 						00 A00-E6	10402700 104027806	0.097	6.5	55.4	-	-	-	-	8	52	5.2 5.2
W	HS	VS	TD	PVC	OUT												
●	●																
Профиль штапика АУРС С48.0636 						00 RAL9016 RAL9006	10408600 10408621 10408631	0.378	6.5	205.3	-	-	-	-	12	78	30.3 32.4 32.4
W	HS	VS	TD	PVC	OUT												
●			●	●	●												
Профиль штапика АУРС С48.0636А 						A00-D6	104099808	0.375	6.5	205.2	-	-	-	-	12	78	30.1
W	HS	VS	TD	PVC	OUT												
●			●	●	●												