


Профиль створки АУРС.СL130.0201
в сборе с усилителем АУРС.СL160.0705, АУРС.СL130.0702

1 : 2



Профиль	m, кг/м.п.	S, мм ²	Jx, см ⁴	Wx, см ³	ay, мм	Jy, см ⁴	Wy, см ³	ax, мм
AYPC.SL130.0201+ AYPC.SL160.0705	2.78	986.14	88.0	13.88	63.39	32.3	6.98	46.29
AYPC.SL130.0201+ AYPC.SL160.0705+ AYPC.SL130.0702	3.96	1468.43	107.7	15.43	69.79	49.8	9.41	52.95
AYPC.SL130.0201+ AYPC.SL160.0705*	2.78	986.14	95.0	14.49	65.58	32.1	6.83	47.03
AYPC.SL130.0201+ AYPC.SL160.0705*+ AYPC.SL130.0702	3.96	1468.43	112.7	15.79	71.36	49.8	9.41	52.95
AYPC.SL130.0201+ AYPC.SL130.0702	3.01	1232.06	32.7	10.87	30.07	42.4	7.62	55.67
AYPC.SL130.0202+ AYPC.SL160.0705	2.08	849.19	62.4	10.39	60.08	8.8	2.64	33.39
AYPC.SL130.0202+ AYPC.SL160.0705*			72.0	10.86	66.27	8.9	2.66	33.5