

6.2 вариант _ HI+ и вариант _ HI with XPS: с пластиковыми рамами F50.1909/1910/1911 с толщиной наружного стекла 6-8мм/F50.1709 с заполнением от 40мм до 74мм; или с толщиной наружного стекла 10-12мм/F50.1710 с заполнением от 44мм до 74мм **для интегрированного окна:**

Clamp 40-50mm

14.5 95.6 42

Профили	Длина штанги	Сток	Вид
10-12mm thk Стекло			
F50.1212+F50.1909+F50.1710 Clamp 44-54mm	6800, 6800, 6800mm	29.5	42.0
F50.1212+F50.1910+F50.1710 Clamp 56-66mm	6800, 6800, 6800mm	29.5	42.0
F50.1212+F50.1911+F50.1710 Clamp 68-74mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1909+F50.1710 Clamp 44-54mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1910+F50.1710 Clamp 56-66mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1911+F50.1710 Clamp 68-74mm	6800, 6800, 6800mm	29.5	42.0
F50.1214+F50.1909+F50.1710 Clamp 44-54mm	6800, 6800, 6800mm	29.5	50.5
F50.1214+F50.1910+F50.1710 Clamp 56-66mm	6800, 6800, 6800mm	29.5	50.5
F50.1214+F50.1911+F50.1710 Clamp 68-74mm	6800, 6800, 6800mm	29.5	50.5
6-8mm thk Стекло			
F50.1212+F50.1909+F50.1709 Clamp 40-50mm	6800, 6800, 6800mm	29.5	42.0
F50.1212+F50.1910+F50.1709 Clamp 52-62mm	6800, 6800, 6800mm	29.5	42.0
F50.1212+F50.1911+F50.1709 Clamp 64-74mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1909+F50.1709 Clamp 40-50mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1910+F50.1709 Clamp 52-62mm	6800, 6800, 6800mm	29.5	42.0
F50.1213+F50.1911+F50.1709 Clamp 64-74mm	6800, 6800, 6800mm	29.5	42.0

